

TIME CHANGE INSTRUCTIONS

NEAX 1000 / 1400 / 2000 IVS / 2000 IVS-2 / 2000 IPS With Dterm Series III, Series E and Series i Phones

CAT Mode Procedure: This is to be done while the phone is in an idle state.

1. Press <TRANSFER>
2. Press <CONF>
3. Press *
4. Press <TRANSFER>
5. Press <CONF>
6. Press #
7. "CAT MODE" displayed on LCD
8. Press <REDIAL or LNR/SPD>
9. "COMMAND" displayed on LCD
10. Press 02
11. Press <RECALL>
12. Press 2
13. Press <RECALL>
14. "02>2>Current Time" displayed on LCD
15. Input correct time using military time (HH MM SS)
16. Press <CONF>

NEAX 1000 / 1400 / 2000 IVS / 2000 IVS-2 / 2000 IPS With Dterm Series II Phones

CAT Mode Procedure: This is to be done while the phone is in an idle state.

1. Press <TRANSFER>
2. Press <HOLD>
3. Press *
4. Press <TRANSFER>
5. Press <HOLD>
6. Press #
7. "CAT MODE" displayed on LCD
8. Press <SPEAKER>
9. "COMMAND" displayed on LCD
10. Press 02
11. Press <ANSWER>
12. Press 2
13. Press <ANSWER>
14. "02>2>Current Time" displayed on LCD
15. Input correct time using military time (HH MM SS)
16. Press <HOLD>

TIME CHANGE INSTRUCTIONS

MARK 2

The Clock/Calendar can only be set from the Attendant Multiline Terminal.

1. Press <CNF>
2. Press *
3. <CNF> LED flutters

4. "PROGRAM CLOCK HOUR ???" is displayed on LED
5. Press Hour Setting (example 0,8)
6. Press DSS Key 20

7. "PROGRAM CLOCK MINUTE ???" is displayed on LED
8. Press Minute Setting (example 3,5)
9. Press DSS Key 20

10. "PROGRAM CLOCK DAY ???" is displayed on LED
11. Press Day Setting (example 0,4) (See NOTE 2)
12. Press DSS Key 20

13. "PROGRAM CLOCK MONTH ???" is displayed on LED
14. Press Month Setting (example press line key 7) (See NOTE 1)
15. Press DSS Key 20

16. "PROGRAM CLOCK YEAR ???" is displayed on LED
17. Press Year Setting (example 0,3)
18. Press <ANS> key to enter data

19. <CNF> LED goes off

NOTE 1: Valid Entries

Hour:	00-23
Minute:	00-59
Day:	01-31
Month:	JAN-DEC (set by line key; L1=Jan, L2=Feb, L3=Mar, etc.)

NOTE 2: Day of the Week, Leap Year

Day of the week and leap year will be automatically set by entering month, date and year data.

TIME CHANGE INSTRUCTIONS

Electra Elite 48 / 192 / Electra Professional I / Electra Professional II

The Clock/Calendar can only be set from a Display Multiline Terminal that is connected to Station Port 01 or 02.

1. Press <FEATURE or FNC>
2. Press 9
3. Press #
4. Press current time (example 0,2,1,4)
5. Press <RECALL> to toggle AM/PM
6. When ONLY setting the time, press <FEATURE or FNC> to end the procedure
7. Press <HOLD> to advance to the calendar
8. Press <RECALL> to select the day of the week
9. Press # to move the cursor to the day of the month setting
10. Use the dial pad to enter the day
11. Press <RECALL> to select the month
12. Press # to move the cursor to the year setting
13. Press the last two digits of the year
14. Press <FEATURE or FNC>