

# DECT HANDSET G577

PROFESSIONAL MOBILE HANDSET  
WITH ALARMING, MESSAGING AND  
MULTI-LINE CAPABILITIES



**DECT handset G577 is a sophisticated handset combining mobile unified communications with a range of alarming and messaging capabilities, to facilitate task management, staff/patient safety and rich messaging in various businesses, hospitality and healthcare.**



## DECT HANDSET G577 AT A GLANCE

- > Appealing design, easy to use handset
- > Lightweight and slim line
- > Bright 2-inch high resolution display
- > Rugged belt-clip
- > Large SOS-key for staff safety
- > Drop resistant design and dust and moisture protection
- > Voice messaging
- > Central directory and presence
- > Simple plug-and-play with MicroSD card
- > Very long battery life and standby time
- > Anti-bacterial (G577h version)
- > 4 function (line-) keys
- > USB-C interface



## DECT HANDSET G577 MAIN FEATURES

- > Provides many different call control features which seamlessly integrate with the voice server
- > Offers mobile interaction under all conditions in various demanding environments

- > Valuable unified communications, including central directory access, presence and messaging and alarming features
- > Dedicated programmable keys with LED indication
- > Intuitive color user interface and icon-based menus
- > Single or dual charger allowing an additional battery to be charged and compatible with previous generation chargers
- > Freedom, comfort and flexibility with Bluetooth or wired headset plus vibrate and ringer notification features
- > DECT compliance for high-quality speech and security
- > High-definition audio



## DECT HANDSET G577H HEALTHCARE

- > Anti-bacterial treated plastics, lens and rubber parts
- > Healthcare version in distinctive color (white)
- > Same capabilities as G577



## DECT HANDSET G577(H)

### FEATURES G577

<b>Call handling<sup>1)</sup></b>	Automatic call answer	Call reject option
	Caller log	HD audio
	CLI (name and number support)	Seamless handover
	Last number redial	On-hook number
	Recall/hold (inquiry)	Talk time up to 20 hours
		Standby time up to 160 hours
<b>Design</b>	Robust design for use in professional environments	Dust and water resistance: IP65
	Triple color LED indication for e.g. missed call and MWI	HAC compliant
<b>Directory</b>	Corporate directory	Personal phone book with multiple numbers per contact
<b>Display</b>	Color graphic 2.0" TFT display, 240 x 320 px (65K)	Date & time indication: synchronized with voice server clock
	Illuminated display: on incoming calls and message	Character set: WideChar (UTF-16)
	Power saving mode: display dim lit or completely off	LCD Backlit
<b>Headset</b>	Wired headset support (USB-C)	Bluetooth headset
<b>Keys</b>	12 keypad keys (0..9, *, #) with text mode support	On- and off-hook: 2 separate keys
	4 function keys for speed dialling and menu shortcuts	Power on/off key combined with off-hook key
	Recall (inquiry) key combined with on-hook key	Soft keys: 3, menu dependent function
	Menu navigation keys: up, down, left and right and OK	Increase and decrease volume
	Distinctive SOS alarm key	Menu key
	Keypad backlit	Speakerphone key
<b>Localization</b>	Supported languages: 14	Multiple (RF) power levels
<b>Memory card (optional)</b>	Triple frequency band	
	Storage of configuration and subscription data personal phone book and caller filter	Easy subscription transfer to another handset via memory card programming
	Easy (pre-)installation via memory card programming	Memory card type: MicroSD
	Blocking of changes to the configuration setting	
<b>Menu</b>	Easy menu programming	
<b>Messaging</b>	Messaging (LRMS) support	Message broadcast support
	Priority messaging support: Normal, urgent and emergency	Set-up of voice call to call back number in message
	Message waiting (voicemail)	
<b>Mobility</b>	Antenna diversity	Multiple subscriptions DECT systems: 10
<b>Other features</b>	Automatic key lock	Accessory features: calculator, stopwatch, alarm clock
<b>Sound/Audio</b>	Adjustable ringer volume	Adjustable earpiece/loudspeaker volume
	Loudspeaker mode/hands free	Microphone mute
	Vibrate mode	Silent ring support
<b>Security</b>	Automatic encryption for secure calls	
<b>Service/Maintenance</b>	Software upgrading via air interface <sup>2)</sup>	Backup of local data via memory card
	Software upgrading via USB-C interface	
<b>User data</b>	Internal memory to store configuration data, personal phone book, messages, caller log, caller filter and calendar entries	Optional memory card
<b>User interface</b>	Icon driven menu	Status line indicators in the display
	Configurable LED (4-col) indicator for e.g. missed call and message waiting	Distinctive melodies for external and internal calls, messages and priorities and per phonebook contact
	Ringer tones/melodies: 20	Audible indicators are user selectable
	Selectable display background	

1) Features depend on the capabilities of the voice server and the DECT system used

2) Needs to be supported by the DECT system

## PHYSICAL CHARACTERISTICS G577(H)

<b>Dimensions</b>	Handset: 128 x 49 x 21 mm	
	Charger: 60 x 60 x 30 mm	
	Charger Rack: 462 x 77 x 61 mm	
<b>Weight</b>	Handset: 144 g	
	Charger: 60 g	
	AC Adapter: 25 g	
<b>Protection</b>	Handset: IP65	
<b>Range</b>	Indoor: 50 m max <sup>3)</sup>	
	Outdoor: 300 m max <sup>4)</sup>	
<b>Power Supply</b>	Handset: 3.7V, 1100mAh Lithium-ion battery	
	Charger (EU mains plug, USB output)	
	Input: 100-240VAC/50/60Hz/250mA	
	Output: 5VDC/1000mA	
	Charger (UK, US, AU mains plug, USB output) <sup>4)</sup>	
	Input: 100-240VAC/50/60Hz/125mA	
	Output: 5VDC/900mA	
	Charger rack (multi region mains plug, 5 mm DC plug)	
<b>Color and finishing</b>	G577 handset: Black	G577h handset: White
	Desktop charger: Black	Charger rack: Black
<b>Audible indicators</b>	Key click	Charger warning
	Coverage warning	Confirmation tone
<b>Status display line indicators</b>	Battery condition	Message waiting
	Caller filter active	Microphone mute
	Field strength	Missed call
	Key lock active	Ringer off
	Loudspeaker active	
<b>LED indicators</b>	Indicators can be assigned to the indicator LED:	
	Battery low	Text or voice message
	Missed call	Voice message
	Text message	Silent charging
<b>Supported menu languages</b>	Danish, Dutch, English, French, German, Greek, Italian, Norwegian, Polish, Portuguese, Russian, Spanish, Swedish, Turkish	

3) Radio coverage depends on environment and presence of obstacles

4) The main plug contains a changeable part for the different power plugs

## ACCESSORIES

<b>G577 handset accessories</b>	Swivel belt clip attachment and swivel belt clip	
	Belt clip	
	USB-C to 3.5 mm conversion cable	
	Vertical pouch (swivel belt-clip, handset can be used while in pouch)	
	Battery pack	
	Desktop charger with/without spare battery charger and AC adapter	
	Charger rack (6 handsets) with AC adapter	

## TRANSMISSION & FREQUENCY

<b>Transmitted radio RF power</b>	Less than 250 mW <sup>5)</sup>
<b>Average Radio RF power</b>	10 mW
<b>Frequency band EMEA</b>	1880 – 1900 MHz
<b>Frequency band Thailand<sup>6)</sup></b>	1900 – 1906 MHz
<b>Frequency band Latin America<sup>6)</sup></b>	1910 – 1930 MHz
<b>Frequency band North America<sup>6)</sup></b>	1920 – 1930 MHz

5) The transmitted Radio RF power is according to local regulations

6) The G577 handset has a triple frequency band and can be used in the EMEA, American and Thai DECT frequency band

## ENVIRONMENTAL CONDITIONS

<b>Temperature range</b>	Operating: -15°C to +55°C
	Charging: +5°C to +45°C
	Transport: -30°C to +60°C
	Storage: -20°C to +60°C
<b>Relative Humidity</b>	Operating: 10 to 93%
	Transport: 10 to 95%
	Storage: 10 to 93%

## COMPLIANCE

<b>EMC</b>	EN 301 489-1, EN 301 489-6, EN 301 489-17
<b>EMF</b>	EN 50663, EN 62479
<b>RF</b>	EN 300 328, EN 301 406
<b>SAR</b>	EN 61000-4-2, EN 61000-4-3
<b>Safety</b>	EN 62368-1
<b>Bluetooth</b>	Version 4.2
<b>G577h anti-bacterial</b>	ISO22196-2011 (2nd edition)

## COMPATIBILITY

<b>Platform Compatibility</b>	SL Series, SV8xxx, SV9xxx, iS3000/SIP@Net, 3C
-------------------------------	---

## DIRECTIVES & REGULATIONS

<b>EMC</b>	2014/30/EU - Electromagnetic Compatibility
<b>LVD</b>	2014/35/EU - Low Voltage Directive
<b>RED</b>	2014/53/EU - Radio Equipment Directive
<b>RoHS</b>	2011/65/EU - Restriction of the use of certain hazardous substances in EEE
<b>WEEE</b>	2012/19/EU - Waste Electrical and Electronic Equipment
<b>ERP</b>	2009/125/EC - Eco-design requirements for Energy-related Products (ErP)

## PACKAGE CONTENT

<b>G577 package content</b>	G577 handset with belt clip Lithium-ion battery pack
-----------------------------	---



DECT HANDSET G577(H)



USB-C to 3.5 mm conversion cable



Charger rack (6 handsets) with AC adapter

The G577h has been designed for healthcare. Special substances have been added to the plastics, lens and rubber parts in order to minimize the risk of bacterial infections. The handset can be cleaned with agents commonly used in healthcare institutes. The placing of the keys allows easy cleaning of the keypad surface.



G577h Desktop Charger with adapter

**G577H ANTIBACTERIAL CHARACTERISTICS**

<b>Plastic parts</b>	BactiBlock®: 920 B0
<b>Clip rubber grip</b>	SteriTouch®: ST10210
<b>Rubber parts</b>	SteriTouch®: ST1012
<b>Lens coating</b>	SteriTouch®: ST1007

**G577/G577H RESISTANCE TO CLEANING LIQUIDS**

<b>Resistance to fluids</b>	M-alcohol (85% methylated ethanol) EN
	Paints and varnishes
	Determination of resistance to liquids
	Part 4: Spotting methods
<b>Liquids:</b>	99% concentration of isopropyl alcohol
	Undiluted dishwasher detergent
	3% Hydrochloric Acid
	M-alcohol (85% methylated ethanol)
	60% Chlorhexidin 0.5mg/ml

NEC and the NEC logo are trademarks or registered trademarks of NEC Corporation that may be registered in Japan and other jurisdictions. All trademarks identified with © or TM are registered trademarks or trademarks of their respective owners. Models may vary for each country, and due to continuous improvements this specification is subject to change without notice. Please refer to your local NEC representative(s) for further details.

**Americas (U.S., Canada, Latin America)**  
 NEC Corporation of America  
[www.necam.com](http://www.necam.com)

For further information please contact NEC Corporation of America or: